

## PRODUCT DATA

7 07 92 00 **Joint Sealants**

# GOLD LABEL ALL SEASON LOOP SEALANT

**Polyester traffic-detector loop sealant****Description**

Gold Label All Season Loop Sealant is a self-leveling polyester sealant. It is designed for the traffic-control industry to embed and protect detector loop wire for traffic signals and parking gates.

**Yield**

See page 3 for chart.

**Packaging**

3.5 gallon (30 lb [13.5 kg]) plastic pails, containing:  
1 gallon (3.8 L) liquid  
20 lbs (9 kg) powder  
1/2 oz tube of Flexgard Retarder

**Color**

Gray

**Shelf Life**

1 year when properly stored.

**Storage**

Store and transport in unopened containers at 60 to 80° F (16 to 27° C) in clean, dry conditions.

**Features**

- Cures quickly
- Flexible
- Variable mix ratio
- Self-leveling
- Freeze/thaw tolerant
- Moisture tolerant

**Benefits**

- Minimizes traffic disruption
- Cured sealant accommodates normal movement in concrete or asphalt
- Allows applicator to mix to desired consistency
- Ensures loop wire is totally encapsulated
- Can be used in subfreezing conditions
- Can be used on damp substrates

**Where to Use**

## APPLICATION

- For embedding detector loop wire for traffic signals and parking gates

## LOCATION

- Interior or exterior

## SUBSTRATE

- Concrete and masonry

**How to Apply****Mixing**

1. Gradually add the powder to the liquid resin in a clean container, preferably plastic. Use the full 20 lbs (9 kg) of powder and mix with the 1 gallon (3.8 L) of resin supplied. Extra resin (up to an additional gallon) may be added to meet job requirements. Additional powder may also be added for variable consistency.
2. Stir constantly to achieve a uniform consistency. For best results, use a mechanical mixer.
3. To extend the pot life, mix in the tube of Flexgard provided with each kit.

**Application**

1. Saw cut the joint to desired dimensions.
2. Clear sawcut of water and debris using oil-free compressed air.
3. Install the detector loop wire.
4. Slowly pour Gold Label All Season Loop Sealant into the sawcut, allowing the sealant to settle and self-level.

**Clean Up**

Clean up tools and equipment with lacquer thinner. Clean skin immediately with soap and water or industrial hand cleaner, not solvents.

## Technical Data

### Composition

Gold Label All Season Loop Sealant is a self-leveling polyester sealant.

### Typical Properties

PROPERTY	VALUE
<b>Pot life</b> , min, at 77° F (25° C)	10 – 15
<b>With Flexlard</b>	30 – 40
<b>Initial cure</b> , min, at 77° F (25° C)	20
<b>Cure with Flexlard</b>	45

### Test Data

PROPERTY	RESULTS	TEST METHODS
<b>Viscosity</b> , cps, at 78° F (26° C)	6,500	ASTM Brookfield Model RVT #3 at 10 rpm
<b>Hardness</b> , Shore D	50	ASTM D 2240
<b>Tensile strength</b> , psi (MPa)		ASTM D 638
2 to 1 powder / resin	395 (2.7)	
1 to 1 powder / resin	246 (1.7)	
<b>Elongation</b> , %		ASTM D 638
2 to 1 powder / resin	10	
1 to 1 powder / resin	20	
<b>Bond to concrete</b> , psi (MPa), direct tensile	300 (2.1) 100% concrete failure	ASTM D 4541
<b>Absorption</b> , %		ASTM D 570
Salt water (5% solution)	0.20	
Water	0.20	
Oil	0.02	
Gasoline	0.80	
<b>Linear shrinkage</b> , %	0.78	ASTM D 2566
<b>Arc resistance</b> , sec	181	ASTM D 495

All application and performance values are typical for the material, but may vary with test methods, conditions, and configurations.

## For Best Performance

- Can be applied below freezing temperatures provided substrate is frost and ice free.
- Make certain the most current versions of product data sheet and MSDS are being used; call Customer Service (1-800-433-9517) to verify the most current version.
- Proper application is the responsibility of the user. Field visits by BASF personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

## Health and Safety

### GOLD LABEL ALL SEASON LOOP SEALANT LIQUID

#### Warning

Gold Label All Season Loop Sealant Liquid contains styrene.

#### Risks

Flammable liquid and vapor. May cause skin and eye irritation. Ingestion may cause irritation. May be absorbed through skin. Repeated or prolonged exposure increases risk of exposure. Inhalation of vapors may cause irritation and intoxication with headaches, dizziness and nausea. Reports associate repeated or prolonged occupational overexposure to solvents with permanent brain, nervous system, liver and kidney damage. INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

#### Precautions

KEEP OUT OF THE REACH OF CHILDREN. KEEP AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION. Vapors are heavier than air. Keep container closed. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash

thoroughly after handling. Avoid breathing vapors. DO NOT take internally. Use impervious gloves, eye protection and if the TLV is exceeded or used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable federal, state and local regulations.

#### First Aid

In case of eye contact, flush thoroughly with water for at least 15 minutes. SEEK IMMEDIATE MEDICAL ATTENTION. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.


Refer to Material Safety Data Sheet (MSDS) for further information.

#### Proposition 65

This product contains materials listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

#### VOC Content

2.74 lbs/gal or 329 g/L, less water and exempt solvents.



#### GOLD LABEL ALL SEASON LOOP SEALANT

##### Caution

Gold Label All Season Loop Sealant Powder contains limestone, magnesium carbonate, iron oxide and crystalline quartz silica.

##### Risks

May cause skin or eye irritation. Ingestion or inhalation of dust may cause irritation. Contains a small amount of free respirable quartz, which has been listed as a suspected human carcinogen by NTP and IARC. Repeated or prolonged overexposure to free respirable quartz may cause silicosis or other serious and delayed lung injury.

##### Precautions

KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with skin, eyes and clothing. Prevent inhalation of dust. Wash thoroughly after handling. Keep container closed when not in use. DO NOT take internally. Use only with adequate ventilation. Use impervious gloves, eye protection and if the TLV is exceeded or used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable federal, state and local regulations.

##### First Aid

In case of eye contact, flush thoroughly with water for at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION.

For more information see Material Safety Data Sheet (MSDS) for this product.

##### Proposition 65

This product contains material listed by the state of California as known to cause cancer, birth defects, or other reproductive harm.

##### VOC Content

0 lbs/gal or 0 g/L, less water and exempt solvents

**For medical emergencies only,  
call ChemTrec (1-800-424-9300).**

**BASF Construction Chemicals, LLC –  
Building Systems**

889 Valley Park Drive  
Shakopee, MN, 55379

[www.BuildingSystems.BASF.com](http://www.BuildingSystems.BASF.com)

**Customer Service** 800-433-9517  
**Technical Service** 800-243-6739



**LIMITED WARRANTY NOTICE:** Every reasonable effort is made to apply BASF exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

**For professional use only. Not for sale to or use by the general public.**

Form No. 1018959 9/07  
Printed on recycled paper including 10% post-consumer fiber.

© 2007 BASF  
Printed in U.S.A.