

12" Pedestrian Signal Aluminum and Polycarbonate

Available in both international symbol and word legends

Designed for low maintenance and increased durability

Uses Standard Traffic Signal lamps

Completely Compatible with Standard Signal Hardware



GENERAL:

McCain pedestrian heads are designed to meet and exceed ITE standards. They offer low maintenance and increased durability and are completely compatible with standard signal hardware.

ALUMINUM SIGNALS:

Die cast from aluminum alloy. Our in house die casting foundry allows us complete control in maintaining the highest quality.

POLY SIGNALS:

Injection molded from ultraviolet and heat stabilized, flame retardant, permanently colored polycarbonate resins.

DOOR AND MOUNTING:

Injection molded from the same materials used in our polycarbonate signals (Aluminum door is not available). Each door has two integrated hinge lugs mounted to the housing with two stainless steel hinge pins. Positive latching is achieved with stainless steel eyebolts and wingnut assemblies. A moisture proof and dust tight seal is assured with an E.P.D.M. rubber gasket fitted into the gasket channel molded into the perimeter of the door.

REFLECTOR ASSEMBLY:

Bright specular aluminum, mounted to a swing out frame. Coupling the lamp socket to the assembly is a spring loaded bail wire. This design allows the removal and adjustment possible without the use of any tools.

LENS:

Injection molded from ultraviolet and heat stabilized flame retardant polycarbonate. The unit is available with ITE approved international symbol "Hand/Man" and "Walk/Don't Walk" legends. The "Hand/Don't Walk" is Portland Orange in color and the "Man/Walk" is lunar white in color.

VISORS:

Molded from extruded ABS sheet and attached to the pedestrian door with six stainless steel screws. They are available in tunnel or cutaway style as specified.

PAINTING:

All exposed aluminum signal surfaces shall be cleaned and powder coated. Standard colors are Dark Olive Green FS595A 14056; Fed Yellow FS595A 13538; Dull Black FS595A 37038. Custom colors are available upon request. Ask for a color chart when ordering.

TERMINAL BLOCK:

Each signal is provided with a 6 section 12 terminal barrier strip. One sided with a "quick disconnect" terminal for socket leads. The opposite with a screw clamp terminal for field wiring.

WARRANTY:

The 12" Ped Signal is warranted against defect in materials or workmanship for a period of one (1) year from the date of original shipment.

McCain reserves the right to change product specifications without notice 9/07



2365 Oak Ridge Way Vista, CA 92081, USA
Phone 760-727-8100 Fax 760-727-8264
www.mccain-inc.com